ltc

crevin

5 years guarantee • sanitized (antimicrobial)

General Information



Composition 53%PES 20%PP 18%PES REC 5%OF REC 4%CO REC

Width 140 + 4cm

Weight 580 gr/m2 ± 5 % 812 gr/lm ± 5 %

Custom code UE: 5407.73.00 USA: 5407.73.20.60

Laboratory test number IN-00886-2019-B 2020AN1320 EN ISO 20743

Environmental considerations

ecvcled varn

18% GRS recycled PET bottles

20% Low impact yarn (PP)

4% Recycled CO

53% PES

5% Circular yarn from own waste

Designed and Crafted in Terrassa (Barcelona)

Specifications

Seam slippage resistance (mm) Warp: 1,80 Weft: 2,00 EN ISO 13936/2:2004

Abrasion resistance (End point) >100.000 EN ISO 12947-2:1998

Abrasion resistance (change of aspect: 3000 cycles) 4-5 EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)

Pilling resistance 4-5 EN ISO 12945/2:2000

Lightfastness 5-6 EN ISO 105-B02:1998

Colour fastness to rubbing Dry: <u>4-5</u> Wet: <u>4-5</u> EN ISO 105-X12:2002


Notes:

Ito is woven with a bouclé yarn that creates a natural, irregular surface effect. Bouclé fabrics are generally more sensitive to wear effects than flat wovens, and with intensive or prolonged use may take on a more pronounced texture.

Care

PERFORMANCE+ Easy to clean, longlasting fabrics

Washing conditions



Soiling and cleanability 3-4 FORD FLTM BN 112-08:2005

Dimensional change domestic washing and drying (%) Warp: <u>-3</u> Weft: <u>-3</u>

When confectioning or washing the sofa cover with velcro please attach a protective cloth.

Antibacterial activity Strong antibacterial property >3 EN ISO 20743:2013



Ignitability

BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013

BS5852 Source 1 EN1021-Part 2:2006 UNI 9175 Clase 3IM

Life cycle analysis

Cradle to gate assessment. From raw material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling.



Water consumption



Certificates



UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH

Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa

Study realized in collaboration with UPC

Methodology: Life Cycle Analysis. ISO 14040 standard.

Database[.] Own data, Ecoinvent 3.6 database and published data.

Functional unit: 1 linear meters, 140 cm width.

Calculation methodology: ReCiPe Midpoint (H) 2016 v1.0 ReCiPe Endpoint (H) 2016 v1.04 IPCC 2013 GWP 100a v1.03



Rev. nº:15 - 20/07/2022 *Results have been obtained by Crevin's internal laboratory and must therefore be seen as indicative.

Carbon footprint