


5 years guarantee • easy to clean • durability

General Information	Specifications	Care
 Composition 53%PES 20%PP 18%PES REC 5%OF REC 4%CO REC Width 140 + 4cm Weight 580 gr/m² ± 5 % 812 gr/lm ± 5 % Custom code UE: 5407.73.00 USA: 5407.73.20.60 Laboratory test number IN-00886-2019-B 2020AN1320 EN ISO 20743	Seam slippage resistance (mm) Warp: 1,80 Weft: 2,00 EN ISO 13936/2:2004 Abrasion resistance (End point) >100.000 EN ISO 12947-2:2016 Abrasion resistance (change of aspect: 3000 cycles) 4-5 EN ISO 12947/4:1998 and EN 14465:2003 (Annex A) Pilling resistance 4-5 EN ISO 12945/2:2000 Lightfastness 5-6 EN ISO 105-B02:1998 and 105 B02/A01:2002 Colour fastness to rubbing Dry: 4-5 Wet: 4-5 EN ISO 105-X12:2002 Notes: Ito is woven with a bouclé yarn that creates a natural, irregular surface effect. Bouclé fabrics are generally more sensitive to wear effects than flat wovens, and with intensive or prolonged use may take on a more pronounced texture.	PERFORMANCE+ Easy to clean, longlasting fabrics Washing conditions  Soiling and cleanability 3-4 FORD FLTM BN 112-08:2005 Dimensional change domestic washing and drying (%) Warp: -3 Weft: -3 EN ISO 3759:2008, EN ISO 6330:2000 and EN ISO 5077:2008 When confectioning or washing the sofa cover with velcro please attach a protective cloth.
		Ignitability BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013 Upon Request: BS5852 Source 1 EN1021-Part 2:2006 BS 7176 Low Hazard UNI 9175 Clase 3IM

Environmental considerations

 27% recycled yarn 18% GRS recycled PET bottles 5% Circular yarn from own waste 4% Recycled CO 20% Low impact yarn (PP) 53% PES	Life cycle analysis Cradle to gate assessment. From raw material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling.	 UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa Study realized in collaboration with UPC Methodology: Life Cycle Analysis. ISO 14040 standard. Functional unit: 1 linear meters, 140 cm width. Database: Own data, Ecoinvent 3.6 database and published data. Calculation methodology: Aware V1.02 ReCiPe Midpoint (H) 2016 v1.04 ReCiPe Endpoint (H) 2016 v1.04 IPCC 2013 GWP 100a v1.03 Software: SimaPro 9.4.0.1
	Carbon footprint 5,35 kg CO₂ eq / m 9,48% less since 2020 Water consumption 115,1 liters / m 18,96% less since 2020	

Designed and Crafted
in Terrassa (Barcelona)