


fire resistant • easy to clean • durability

General Information	Specifications	Care		
 Composition 65%PES 14%MA 11%CO REC 10%PES REC Width 140 + 4cm Weight 606 gr/m2 ± 5 % 848 gr/lm ± 5 % Custom code UE: 5801.36.00 USA: 5801.36.00.20 Laboratory test number IN-00474-2022-1	Seam slippage resistance (mm) Warp: 1,8 Weft: 1,3 EN ISO 13936/2:2004 Abrasion resistance (Full worn off) 100.000 EN ISO 12947-2:2021 Abrasion resistance (change of aspect: 3000 cycles) 3-4 EN ISO 12947/4:1998 and EN 14465:2003 (Annex A) Pilling resistance 4-5 EN ISO 12945/2:2000 Lightfastness 5-6 EN ISO 105-B02:1998 and 105 B02/A01:2002 Colour fastness to rubbing Dry: 4-5 Wet: 4-5 EN ISO 105-X12:2002	PERFORMANCE+ Easy to clean, longlasting fabrics Washing conditions  Soiling and cleanliness 4-5 FORD FLTM BN 112-08:2005 Dimensional change domestic washing and drying (%) Warp: -1 Weft: -1 EN ISO 3759:2008, EN ISO 6330:2000 and EN ISO 5077:2008 When confectioning or washing the sofa cover with velcro please attach a protective cloth. Ignitability <table><tr><td>BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013</td><td>BS5852 Source 1 EN1021-Part 2:2006 BS 7176 Low Hazard UNI 9175 Clase 3IM</td></tr></table>	BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013	BS5852 Source 1 EN1021-Part 2:2006 BS 7176 Low Hazard UNI 9175 Clase 3IM
BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013	BS5852 Source 1 EN1021-Part 2:2006 BS 7176 Low Hazard UNI 9175 Clase 3IM			

Environmental considerations

 11%CO recycled 10% GRS recycled PET bottles 65% PES 14% MA	Life cycle analysis Cradle to gate assessment. From raw material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling. Carbon footprint 5,4 kg CO₂ eq /m 0,37% less since 2020 Water consumption 105,12 liters/m 9,46% less since 2020	UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa Study realized in collaboration with UPC Methodology: Life Cycle Analysis. ISO 14040 standard. Functional unit: 1 linear meters, 140 cm width. Database: Own data, Ecoinvent 3.6 database and published data. Calculation methodology: Aware V1.02 ReCiPe Midpoint (H) 2016 v1.04 ReCiPe Endpoint (H) 2016 v1.04 IPCC 2013 GWP 100a v1.03 Software: SimaPro 9.4.0.1
--	--	---

Designed and Crafted
in Terrassa (Barcelona)

